

Package ‘OmicSense’

September 22, 2023

Type Package

Title Biosensor Development using Omics Data

Version 0.2.0

Maintainer Takahiko Koizumi <takahiko.koizumi@gmail.com>

Description A method for the quantitative prediction using omics data.
This package provides functions to construct the quantitative prediction model using omics data.

Depends R (>= 3.5.0)

License GPL (>= 3)

Language en-US

Encoding UTF-8

LazyData true

RoxygenNote 7.2.3

Suggests knitr, rmarkdown, testthat (>= 3.0.0)

URL <<https://github.com/takakoizumi/OmicSense>>

VignetteBuilder knitr

Config/testthat/edition 3

Imports ggplot2, kernlab

NeedsCompilation no

Author Takahiko Koizumi [aut, cre],
Kenta Suzuki [ctb],
Yasunori Ichihashi [ctb]

Repository CRAN

Date/Publication 2023-09-22 21:30:08 UTC

R topics documented:

os.clean	2
os.pca	3

os.pred	4
os.rank	5
os.sort	6
Pinus	7
Index	8

os.clean	<i>Clean data by eliminating predictors with many missing values</i>
----------	--

Description

Clean data by eliminating predictors with many missing values

Usage

```
os.clean(x, missing = 0.1, lowest = 10)
```

Arguments

x	A data matrix (row: samples, col: predictors).
missing	A ratio of missing values in each column allowed to be remained in the data.
lowest	The lowest value to be leaved in the data.

Value

A data matrix (row: samples, col: qualified predictors)

Author(s)

Takahiko Koizumi

Examples

```
data(Pinus)
train.raw <- Pinus$train
ncol(train.raw)

train <- os.clean(train.raw)
ncol(train)
```

`os.pca`*Visualize predictors using principal coordinate analysis*

Description

Visualize predictors using principal coordinate analysis

Usage

```
os.pca(x, y, method = "linear", thresh = 0, n.pred = ncol(x), size = 1)
```

Arguments

<code>x</code>	A data matrix (row: samples, col: predictors).
<code>y</code>	A vector of target value.
<code>method</code>	A string to specify the regression function for calculating R-squared values. "linear" (default), "quadratic" or "cubic" function can be specified.
<code>thresh</code>	The lower threshold of R-squared value to be indicated in a PCA plot (default: 0).
<code>n.pred</code>	The number of candidate predictors for prediction model to be indicated in a PCA plot (default: <code>ncol(x)</code>).
<code>size</code>	The size of symbols in a PCA plot (default: 1).

Value

A PCA plot

Author(s)

Takahiko Koizumi

Examples

```
data(Pinus)
train <- os.clean(Pinus$train)
target <- Pinus$target
os.pca(train, target)
```

`os.pred`*Construct and apply the OmicSense model with your own data*

Description

Construct and apply the OmicSense model with your own data

Usage

```
os.pred(x, y, newx = x, method = "linear", thresh = 0, n.pred = 0)
```

Arguments

<code>x</code>	A data matrix (row: samples, col: predictors).
<code>y</code>	A vector of target value.
<code>newx</code>	A data matrix (row: samples, col: predictors).
<code>method</code>	A string to specify the regression function for calculating R-squared values. "linear" (default), "quadratic" or "cubic" function can be specified.
<code>thresh</code>	The lower threshold of R-squared value to be leaved in prediction model (default: 0).
<code>n.pred</code>	The number of candidate predictors to be leaved in prediction model (default: 30).

Value

A vector of the environment in which the samples of newx were collected

Author(s)

Takahiko Koizumi

Examples

```
data(Pinus)
train <- os.clean(Pinus$train)
test <- Pinus$test
test <- test[, colnames(train)]
target <- Pinus$target
cor(target, os.pred(train, target, newx = test, method = "cubic"))
```

os.rank *Visualize R-squared value distribution in target-predictor relationship*

Description

Visualize R-squared value distribution in target-predictor relationship

Usage

```
os.rank(  
  x,  
  y,  
  method = "linear",  
  thresh = 0,  
  n.pred = ncol(x),  
  upper.xlim = ncol(x)  
)
```

Arguments

x	A data matrix (row: samples, col: predictors).
y	A vector of target value.
method	A string to specify the regression function for calculating R-squared values. "linear" (default), "quadratic" or "cubic" function can be specified.
thresh	The lower threshold of R-squared value to be leaved in prediction model (default: 0).
n.pred	The number of predictors to be leaved in prediction model (default: ncol(x)).
upper.xlim	The upper limitation of x axis (i.e., the number of predictors) in the resulted figure (default: ncol(x)).

Value

A rank order plot

Author(s)

Takahiko Koizumi

Examples

```
data(Pinus)  
train <- os.clean(Pinus$train)  
target <- Pinus$target  
train <- os.sort(train, target)  
os.rank(train, target)
```

os.sort	<i>Sort and select predictors according to the strength of target-predictor relationship</i>
---------	--

Description

Sort and select predictors according to the strength of target-predictor relationship

Usage

```
os.sort(x, y, method = "linear", n.pred = ncol(x), thresh = 1)
```

Arguments

x	A data matrix (row: samples, col: predictors).
y	A vector of target value.
method	A string to specify the regression function for calculating R-squared values. "linear" (default), "quadratic" or "cubic" function can be specified.
n.pred	The number of predictors to be leaved in prediction model (default: ncol(x)).
thresh	The lower threshold of R-squared value to be leaved in prediction model (default: 1).

Value

A data matrix (row: samples, col: sorted predictors)

Author(s)

Takahiko Koizumi

Examples

```
data(Pinus)
train <- os.clean(Pinus$train)
target <- Pinus$target
cor(target, train[, 1])

train <- os.sort(train, target, thresh = 0.5)
cor(target, train[, 1])
```

Pinus

Transcriptomes of Pinus roots under a Temperature Gradient

Description

This dataset gives the TPM values of 200 selected genes obtained from 60 Pinus root samples (30 samples each for training and test data) under a temperature gradient, generated by RNA-seq.

Usage

Pinus

Details

A gene expression data matrix of 30 root samples of *P. thunbergii* under five temperature conditions (8, 13, 18, 23, 28 °C) with six biological replicates is in the first element of the list.

A gene expression data matrix of another 30 root samples of *P. thunbergii* under the same condition is in the second one.

Temperature conditions where 30 root samples in each data matrix were generated are in the third one.

Gene expressions are normalized in the TPM value.

Source

original (not published)

References

original (not published)

Index

* **dataset**

Pinus, 7

os.clean, 2

os.pca, 3

os.pred, 4

os.rank, 5

os.sort, 6

Pinus, 7