

Package ‘grepreaper’

January 23, 2026

Title Efficient Data Filtering and Aggregation Using Grep

Version 0.1.0

Description Provides an interface to the system-level 'grep' utility for efficiently reading, filtering, and aggregating data from multiple flat files. By pre-filtering data at the command line before it enters the R environment, the package reduces memory overhead and improves ingestion speed. Includes functions for counting records across large file systems and supports recursive directory searching.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.3

Suggests ggplot2, knitr, rmarkdown

VignetteBuilder knitr

Imports data.table, methods

NeedsCompilation no

Author David Shilane [aut],
Atharv Raskar [aut],
Akshat Maurya [aut, cre]

Maintainer Akshat Maurya <codingmaster902@gmail.com>

Repository CRAN

Date/Publication 2026-01-23 21:10:02 UTC

Contents

build_grep_cmd	2
grep_count	2
grep_read	3
split_columns	5

Index

7

build_grep_cmd	<i>Build grep command string</i>
----------------	----------------------------------

Description

Constructs a safe and properly formatted grep command string for system execution. This function handles input sanitization by utilizing R's internal shell quoting mechanism, ensuring compatibility across different operating systems.

Usage

```
build_grep_cmd(pattern, files, options = "", fixed = FALSE)
```

Arguments

pattern	Character vector of patterns to search for.
files	Character vector of file paths to search in.
options	Character string containing grep flags (e.g., "-i", "-v").
fixed	Logical; if TRUE, grep is told to treat patterns as fixed strings.

Value

A properly formatted command string ready for system execution.

grep_count	<i>grep_count: Efficiently count the number of relevant records from one or more files using grep</i>
------------	---

Description

grep_count: Efficiently count the number of relevant records from one or more files using grep

Usage

```
grep_count(
  files = NULL,
  path = NULL,
  file_pattern = NULL,
  pattern = "",
  invert = FALSE,
  ignore_case = FALSE,
  fixed = FALSE,
  recursive = FALSE,
  word_match = FALSE,
  only_matching = FALSE,
```

```

skip = 0,
header = TRUE,
include_filename = FALSE,
show_cmd = FALSE,
show_progress = FALSE,
...
)

```

Arguments

files	Character vector of file paths to read.
path	Optional. Directory path to search for files.
file_pattern	Optional. A pattern to filter filenames when using the path argument. Passed to <code>list.files</code> .
pattern	Pattern to search for within files (passed to grep).
invert	Logical; if TRUE, return non-matching lines.
ignore_case	Logical; if TRUE, perform case-insensitive matching (default: TRUE).
fixed	Logical; if TRUE, pattern is a fixed string, not a regular expression.
recursive	Logical; if TRUE, search recursively through directories.
word_match	Logical; if TRUE, match only whole words.
only_matching	Logical; if TRUE, return only the matching part of the lines.
skip	Integer; number of rows to skip.
header	Logical; if TRUE, treat first row as header.
include_filename	Logical; if TRUE, include source filename as a column.
show_cmd	Logical; if TRUE, return the grep command string instead of executing it.
show_progress	Logical; if TRUE, show progress indicators.
...	Additional arguments passed to fread.

Value

A data.table containing file names and counts.

grep_read

grep_read: Efficiently read and filter lines from one or more files using grep, returning a data.table.

Description

grep_read: Efficiently read and filter lines from one or more files using grep, returning a data.table.

Usage

```
grep_read(
  files = NULL,
  path = NULL,
  file_pattern = NULL,
  pattern = "",
  invert = FALSE,
  ignore_case = FALSE,
  fixed = FALSE,
  show_cmd = FALSE,
  recursive = FALSE,
  word_match = FALSE,
  show_line_numbers = FALSE,
  only_matching = FALSE,
  nrows = Inf,
  skip = 0,
  header = TRUE,
  col.names = NULL,
  include_filename = FALSE,
  show_progress = FALSE,
  ...
)
```

Arguments

files	Character vector of file paths to read.
path	Optional. Directory path to search for files.
file_pattern	Optional. A pattern to filter filenames when using the path argument. Passed to <code>list.files</code> .
pattern	Pattern to search for within files (passed to grep).
invert	Logical; if TRUE, return non-matching lines.
ignore_case	Logical; if TRUE, perform case-insensitive matching (default: TRUE).
fixed	Logical; if TRUE, pattern is a fixed string, not a regular expression.
show_cmd	Logical; if TRUE, return the grep command string instead of executing it.
recursive	Logical; if TRUE, search recursively through directories.
word_match	Logical; if TRUE, match only whole words.
show_line_numbers	Logical; if TRUE, include line numbers from source files. Headers are automatically removed and lines renumbered.
only_matching	Logical; if TRUE, return only the matching part of the lines.
nrows	Integer; maximum number of rows to read.
skip	Integer; number of rows to skip.
header	Logical; if TRUE, treat first row as header. Note that using FALSE means that the first row will be included as a row of data in the reading process.

```

col.names      Character vector of column names.
include_filename Logical; if TRUE, include source filename as a column.
show_progress  Logical; if TRUE, show progress indicators.
...           Additional arguments passed to fread.

```

Value

A data.table with different structures based on the options:

- Default: Data columns with original types preserved
- show_line_numbers=TRUE: Additional 'line_number' column (integer) with source file line numbers
- include_filename=TRUE: Additional 'source_file' column (character)
- only_matching=TRUE: Single 'match' column with matched substrings
- show_cmd=TRUE: Character string containing the grep command

Note

When searching for literal strings (not regex patterns), set `fixed = TRUE` to avoid regex interpretation. For example, searching for "3.94" with `fixed = FALSE` will match "3894" because "." is a regex metacharacter.

Header rows are automatically handled:

- With `show_line_numbers=TRUE`: Headers (line_number=1) are removed and lines renumbered
- Without line numbers: Headers matching column names are removed
- Empty rows and all-NA rows are automatically filtered out

split_columns

Split columns based on a delimiter

Description

Efficiently splits character vectors into multiple columns based on a specified delimiter. This function is optimized for performance and handles common use cases like parsing grep output or other delimited text data.

Usage

```

split_columns(
  x,
  column.names = NA,
  split = ":",
  resulting.columns = 3,
  fixed = TRUE
)

```

Arguments

<code>x</code>	Character vector to split
<code>column.names</code>	Names for the resulting columns (optional)
<code>split</code>	Delimiter to split on (default: ":")
<code>resulting.columns</code>	Number of columns to create (default: 3)
<code>fixed</code>	Whether to use fixed string matching (default: TRUE)

Value

A data.table with split columns. Column names are automatically assigned as V1, V2, V3, etc. unless custom names are provided via `column.names`.

Examples

```
# Split grep-like output with colon delimiter
data <- c("file.txt:15:error message", "file.txt:23:warning message")
result <- split_columns(data, resulting.columns = 3)
print(result)

# With custom column names
result_named <- split_columns(data,
                               column.names = c("filename", "line", "message"),
                               resulting.columns = 3)
print(result_named)

# Split into 2 columns (combining remaining elements)
result_2col <- split_columns(data, resulting.columns = 2)
print(result_2col)
```

Index

`build_grep_cmd`, 2

`grep_count`, 2

`grep_read`, 3

`split_columns`, 5