Section name references in LaTeX*

Sebastian Rahtz (deceased)
Heiko Oberdiek (inactive)
The LaTeX Project
https://github.com/LaTeX-Package-Repositories/nameref

2026-11-03

Contents

1 Introduction **1**

2 Background and advice for package and class authors **1**

3 History **3**

4 Implementation **3**
4.1 \label stuff 4
4.2 Changes of section macros 7
4.2.1 Theorems 9
4.3 Referencing stuff 9
4.4 Usage and frontend 12
4.5 Compatibility with varioref 13
4.6 Support for package listings 13

5 Index **14**

1 Introduction

Cross-referencing to include the *name* of the section, rather than just the number or page. This works by redefining some of the inside LaTeX macros, so it is vulnerable to future changes.

2 Background and advice for package and class authors

The package redefines the `\label` command to write additionally `\@currentlabelname` to the `.aux` file. This can then be referenced with `\nameref`. Package authors who want to support nameref should define this command (locally) in a suitable way.

*This file has version number v2.60, last revised 2026-11-03.

The content should be so that it can be safely written to the `.aux` file. nameref itself uses the package gettitlestring but this is not required.

nameref patches a number of commands (mostly sectioning commands) and environments so that they store `\@currentlabelname`. A class or a package that want to provide native support instead can suppress this patches by defining commands described below. The commands must be defined before the patch is made, in most cases before nameref is loaded, sometimes only before begin document.

sectioning commands Redefined are

- `\@sect`: beside adding a command that stores the title of a sectioning command (if present the optional argument is used) nameref also stores the level number in a counter `section@level` (reason is unknown, only two packages, e-french and pdfscreen seem to use it), and surrounds the text with `\Sectionformat` (only used by acmart, memoir, pdfscreen, pdfslide), a command which takes two argument: the first the text, the second the level.
- `\@ssect`: command to store the title added, `\Sectionformat` is added.
- `\@part`, `\@spart`, `\@chapter`, `\@schapter`: command to store the title added

All the patches excepted the last are disabled if the command `\NR@nopatch@sectioning` is defined (the actual definition is irrelevant, only existence is tested. This currently only suppress the actual patches, the counter, `\Sectionformat` and also the internal copies `\NR@sect` etc are still defined.

captions The following commands are patched

- `\@caption`: command to store the title added. This is done at begin document, but only if hyperref or `\DocumentMetadata` is not detected. With hyperref the patch is done there if `\DocumentMetadata` is not used (and must be disabled in hyperref).

  This patch can be disabled by defining `\NR@nopatch@caption`
- `\LT@c@ption` (from the longtable package): command to store the title added.

  This patch can be disabled by defining `\NR@nopatch@longtable`
- `\lst@MakeCaption` (from the listings package)

  This patch can be disabled by defining `\NR@nopatch@listings`

lists The following command is patched

- `\descriptionlabel`: command to store the label text added. To reference this text the `\label` must be put *inside* the label. This is not compatible with the enumitem package as internal formatting commands are written to the `.aux` file too.

  This patch can be disabled by defining `\NR@nopatch@lists`

theorems

- `\@opargbegintheorem`: command to store the title added.

  This patch can be disabled by defining `\NR@nopatch@theorem`

- `\@begintheorem` (if amsthm is loaded and if the command has a tested meaning): command to store the title added.
  This patch can be disabled by defining `\NR@nopatch@amsthm`

beamer In the beamer class the following commands are patched: `\beamer@section`, `\beamer@subsection`, `\beamer@subsubsection`, `\beamer@descriptionitem` and the template `theorem begin`. If `\NR@nopatch@beamer` is defined nothing is done.

3 History

Sebastian Rahtz, for Lou Burnard, March 15th 1994;
SPQR CERN July 1994;
Last mod. Sept. 3th MG;
Sept. 19th SPQR;
April 11th 1995 SPQR (added section formatting hook);
April 14th 1995 SPQR (compatibility with hyperref);
June 22 1995 SPQR (removed typeout from Sectionformat);
September 22 1997 added varioref hacks by Corey Minyard;
September 28th changes by David Carlisle.
More recent changes are recorded in ChangeLog.

The versions before 2009/11/27 v2.32 did not expand the title strings (of `\section`, `\caption`, …). Then the behaviour switched to expanding, because this allows to remove unwanted macros (`\label`, …). Despite this method is used in package titleref and class memoir, the first feedbacks let me conclude that this is not robust enough. Therefore I wrote package gettitlestring that uses the non-expanding method as default. It also allows me to use this package in package zref-titleref. See the package documentation of package gettitlestring how to change the method. It also provides a hook to remove additional unwanted macros, not supported by the package. Example:

```
\usepackage{gettitlestring}
\GetTitleStringDisableCommands{%
  \let\mylabel\@gobble
  \renewcommand\myindex[2]{}%
}
```

4 Implementation

```
1 ⟨*package⟩
2 \RequirePackage{refcount}[2006/02/12]
3 \RequirePackage{gettitlestring}[2009/12/18]
4 \ExplSyntaxOn
5 \let\NR@GlobalAppendToMacro\tl_gput_right:Nn
6 \ExplSyntaxOff
7
```

In formats older than 2023-06-01 we redefine `\label` so that it also writes the name of the current section to the .aux file; if the name ends in a dot, we zap

it. To allow for the hyperref package, also write fourth and fifth fields (empty by default; used for cross-ref name, and file).

\NR@strip@period

```
\def\NR@strip@period#1.\@empty#2\@nil{#1}
```

\strip@period Macro \strip@period was removed in nameref 2012/07/28 v2.41 and reinserted in 2012/07/31 v2.42 for compatibility reasons with package subfig.

```
\def\strip@period#1.\relax#2\@@@{#1}
```

```
\def\NR@sanitize@labelname{%
  \@onelevel@sanitize\@currentlabelname
  \edef\@currentlabelname{%
    \expandafter\NR@strip@period\@currentlabelname
    \@empty.\@empty\@nil
  }%
}
```

4.1 \label stuff

Here is tested, whether package showkeys is loaded. But if option final is used, the macros of showkeys are not defined, so we have to check an additional test.

\ifNR@showkeys

```
\newif\ifNR@showkeys
\NR@showkeysfalse
\@ifpackageloaded{showkeys}{%
  \begingroup
    \@ifundefined{SK@@label}{%
    }{%
      \global\NR@showkeystrue
    }%
  \endgroup
}{}
```

\label@hook Starting with LaTeX 2023-06-01 it is not longer needed to redefine \label as the kernel provides a hook and stores \@currentlabelname. But as there are packages like ntheorem and revtex which overwrites the kernel definition and then break nameref and hyperref we add a guard. We still support \label@hook for now as it is used below in \slabel and also in hyperref.

```
\providecommand*{\label@hook}{}
\NR@GlobalAppendToMacro{\label@hook}{%
    \NR@sanitize@labelname
    }
\@ifl@t@r\fmtversion{2023-06-01}
  {
   \def\NR@label@copy#1{\@bsphack
     \begingroup
     \UseHookWithArguments{label}{1}{#1}%
     \protected@write\@auxout{}%
         {\string\newlabel{#1}{{\@currentlabel}{\thepage}%
         {\@currentlabelname}{\@currentHref}{\@kernel@reserved@label@data}}}%
  \endgroup
  \@esphack}
```

```
  \@ifl@t@r\fmtversion{2026-06-01}
    {
     \def\NR@label@copy#1{\@bsphack
      \begingroup
      \UseHookWithArguments{label}{1}{#1}%
      \protected@write\@auxout{\let\label\@gobble@om\let\index\@gobble@som\let\glossary\@gob
        {\string\newlabel{#1}{{\@currentlabel}{\thepage}%
        {\@currentlabelname}{\@currentHref}{\@kernel@reserved@label@data}}}%
      \endgroup
      \@esphack
    }}
    {}
  \ifx\label\NR@label@copy
  \else
    \PackageWarning{nameref}{The definition of \string\label\space has changed!
                             \MessageBreak Check your packages!
                             \MessageBreak Replacing it with the kernel definition}
    \let\label\NR@label@copy
    \let\ltx@label\label %for amsmath
  \fi
  \AddToHookWithArguments{label}{\def\label@name{#1}\label@hook}
}
{

\label
  \def\label#1{%
    \@bsphack
    \begingroup
      \def\label@name{#1}%
      \label@hook
      \protected@write\@auxout{}{%
        \string\newlabel{#1}{%
          {\@currentlabel}%
          {\thepage}%
          {\@currentlabelname}%
          {\@currentHref}{}%
        }%
      }%
    \endgroup
    \@esphack
  }%
  \ifNR@showkeys
    \def\label#1{%
      \@bsphack
      \SK@\SK@@label{#1}%
      \begingroup
        \def\label@name{#1}%
        \label@hook
        \protected@write\@auxout{}{%
          \string\newlabel{#1}{%
            {\@currentlabel}%
            {\thepage}%
            {\@currentlabelname}%
```

```
              {\@currentHref}{}%
            }%
          }%
        \endgroup
        \@esphack
      }%
    \fi
  }
```

`\ltx@label` Starting with LaTeX 2023-06-01 it is not longer needed to update the amsmath command `\ltx@label` as nameref no longer changes `\label`

```
\@ifl@t@r\fmtversion{2023-06-01}
  {}{\let\ltx@label\label}
```

Needed for the *subeqnarray* package.

`\slabel`

```
\@ifundefined{slabel}{}{%
  \def\slabel#1{%
    \@bsphack
    \if@filesw
      \begingroup
        \def\label@name{#1}%
        \label@hook
        \let\thepage\relax
        \def\protect{\noexpand\noexpand\noexpand}%
        \edef\@tempa{%
          \write\@auxout{%
            \string\newlabel{#1}{%
              {\thesubequation}%
              {\thepage}%
              {\@currentlabelname}%
              {\@currentHref}{}%
            }%
          }%
        }%
      \expandafter\endgroup
      \@tempa
      \if@nobreak\ifvmode\nobreak\fi\fi
    \fi
    \@esphack
  }%
}
```

Overload an AMS LaTeX command, which uses `\newlabel`. Sigh!

`\@writetocindents@`

```
\def\@writetocindents@{%
  \begingroup
  \@for\@tempa:=-1,0,1,2,3\do{%
    \immediate\write\@auxout{%
      \string\newlabel{tocindent\@tempa}{%
        \csname r@tocindent\@tempa\endcsname{}{}{}{}%
      }%
```

```
    }%
  }%
  \endgroup
}
```

4.2 Changes of section macros

Add to the underlying section heading macros so that they note the section name for use by label.

If a section heading or the like has a `\label` in it, we need to extract it, or subsequent processing breaks.

`\NR@gettitle`

```
\def\NR@gettitle#1{%
  \GetTitleString{#1}%
  \let\@currentlabelname\GetTitleStringResult
}
```

First the numbered sections. While we are about it, put in a useful section formatting macro.

`\NR@sect`

```
\let\NR@sect\@sect
```

```
\newcounter{section@level}
```

`\@sect`

```
\@ifundefined{NR@nopatch@sectioning}
 {\def\@sect#1#2#3#4#5#6[#7]#8{%
   \setcounter{section@level}{#2}%
   \NR@gettitle{#7}%
   \NR@sect{#1}{#2}{#3}{#4}{#5}{#6}[{#7}]{\Sectionformat{#8}{#2}}%
 }}{}
```

and now the unnumbered ones

`\NR@ssect`

```
\let\NR@ssect\@ssect
```

`\@ssect`

```
\@ifundefined{NR@nopatch@sectioning}
 {\def\@ssect#1#2#3#4#5{%
   \NR@gettitle{#5}%
   \NR@ssect{#1}{#2}{#3}{#4}{\Sectionformat{#5}{#1}}%
 }}{}
```

Parts and chapters are treated differently. sigh. `\@part` and `\@spart` are `\long` because of class memoir.

```
\let\NR@part\@part
\let\NR@spart\@spart
\let\NR@chapter\@chapter
\let\NR@schapter\@schapter
\@ifundefined{NR@nopatch@sectioning}
```

```
{%
 \long\def\@part[#1]#2{%
   \NR@gettitle{#1}%
   \NR@part[{#1}]{#2}%
 }
 \long\def\@spart#1{%
   \NR@gettitle{#1}%
   \NR@spart{#1}%
 }
 \def\@chapter[#1]#2{%
   \NR@gettitle{#1}%
   \NR@chapter[{#1}]{#2}%
 }
 \def\@schapter#1{%
   \NR@gettitle{#1}%
   \NR@schapter{#1}%
 }}{}
```

Captions

```
\AtBeginDocument{%
 \@ifundefined{NR@nopatch@caption}
  {
    \@ifpackageloaded{hyperref}
      {
        \IfDocumentMetadataT
         {
           \let\NR@@caption\@caption
           \long\def\@caption#1[#2]{%
            \NR@gettitle{#2}%
            \NR@@caption{#1}[{#2}]}
         }
      }
      {
        \let\NR@@caption\@caption
        \long\def\@caption#1[#2]{%
         \NR@gettitle{#2}%
         \NR@@caption{#1}[{#2}]}
      }
  }
  {}
 \@ifpackageloaded{longtable}{%
  \@ifundefined{NR@nopatch@longtable}
   {%
     \let\NRorg@LT@c@ption\LT@c@ption
     \def\LT@c@ption#1[#2]#3{%
      \NRorg@LT@c@ption{#1}[{#2}]{#3}%
      \def\@tempa{#2}%
      \ifx\@tempa\@empty
      \else
       \NR@gettitle{#2}%
      \fi
     }%
   }{}%
 }{}%
```

Environment ‘description’.

```
  \@ifundefined{descriptionlabel}{%
  }{%
    \@ifundefined{NR@nopatch@lists}
     {\let\NRorg@descriptionlabel\descriptionlabel
      \def\descriptionlabel#1{%
       \NR@gettitle{#1}%
       \NRorg@descriptionlabel{#1}%
       }%
     }{}%
  }%
}
```

4.2.1 Theorems

```
\@ifundefined{NR@nopatch@theorem}{%
 \@ifundefined{@opargbegintheorem}{}{%
   \let\NRorg@opargbegintheorem\@opargbegintheorem
   \def\@opargbegintheorem#1#2#3{%
     \NR@gettitle{#3}%
     \NRorg@opargbegintheorem{#1}{#2}{#3}%
   }%
 }
}{}
\@ifundefined{NR@nopatch@amsthm}{%
\AtBeginDocument{%
  \@ifpackageloaded{amsthm}{%
    \let\NRorg@begintheorem\@begintheorem
    \begingroup
      \edef\x{macro:\string#1\string#2[\string#3]}%
      \@onelevel@sanitize\x
      \def\y#1->#2\@nil{#1}%
      \edef\z{\expandafter\y\meaning\@begintheorem->\@nil}%
      \@onelevel@sanitize\z
    \expandafter\endgroup
    \ifx\x\z
      \def\@begintheorem#1#2[#3]{%
        \NR@gettitle{#3}%
        \NRorg@begintheorem{#1}{#2}[{#3}]%
      }%
    \fi
  }{}%
}}{}
```

4.3 Referencing stuff

We default the label and hypertext reference to be empty.

```
\providecommand*{\@currentlabelname}{}
\providecommand*{\@currentHref}{}
```

Since the second part of the preserved reference now has five parts (number, page, name, hypertext reference and file), we need extra utility macros:

`\@firstoffive`

```
\long\def\@firstoffive#1#2#3#4#5{#1}
```

```
\@secondoffive
\long\def\@secondoffive#1#2#3#4#5{#2}
\@thirdoffive
\long\def\@thirdoffive#1#2#3#4#5{#3}
\@fourthoffive
\long\def\@fourthoffive#1#2#3#4#5{#4}
\@fifthoffive
\long\def\@fifthoffive#1#2#3#4#5{#5}
```

We have to redefine `\ref`, `\Ref` and `\pageref` to know about extra reference elements. Make them robust, and compatible with Babel. We also define starred versions so that it doesn't depend on hyperref if they are defined or not. We use the same internal names as hyperref. The Babel switch is mimicked if not already defined. Some support for package showkeys is implemented. If option `notref` of that package is set, `\SK@ref` has the meaning of `\@empty`.

```
\@safe@activestrue
\providecommand*\@safe@activestrue{}%
\@safe@activesfalse
\providecommand*\@safe@activesfalse{}%
\NR@ref@showkeys
\newcommand\NR@ref@showkeys[1]{}%
\NR@setref
\def\NR@setref#1{%
  \begingroup
    \@safe@activestrue
    \expandafter
  \endgroup
  \expandafter\NR@@setref\csname r@#1\endcsname
}
\NR@@setref
\def\NR@@setref#1{%
  \ifx\@undefined#1%
    \let#1\relax
  \fi
  \@setref#1%
}
\T@ref
\def\T@ref#1{%
  \NR@ref@showkeys{#1}%
  \NR@setref{#1}\@firstoffive{#1}%
}%
```

\@refstar

```
\def\@refstar#1{%
  \NR@ref@showkeys{#1}%
  \NR@setref{#1}\@firstoffive{#1}%
}%
```

\T@pageref

```
\def\T@pageref#1{%
  \NR@ref@showkeys{#1}%
  \NR@setref{#1}\@secondoffive{#1}%
}%
```

\@pagerefstar

```
\def\@pagerefstar#1{%
  \NR@ref@showkeys{#1}%
  \NR@setref{#1}\@secondoffive{#1}%
}%
```

\T@Ref

```
\def\T@Ref#1{%
    \NR@ref@showkeys{#1}%
    \NR@setref{#1}\NR@MakeUppercaseFirstOfFive{#1}%
  }%
\def\NR@MakeUppercaseFirstOfFive#1#2#3#4#5{%
    \MakeUppercase#1%
  }%
```

\@Refstar

```
\def\@Refstar#1{%
    \NR@ref@showkeys{#1}%
    \NR@setref{#1}\NR@MakeUppercaseFirstOfFive{#1}%
  }%

\ifNR@showkeys
  \ifx\SK@ref\@empty
  \else
  \renewcommand\NR@ref@showkeys[1]{%
    \@safe@activestrue
    \SK@\SK@@ref{#1}%
    \@safe@activesfalse}
  \fi
\fi
```

Package hyperref uses the same definitions of \ref, \Ref and \pageref but has to redefine the non-starred command to add the hyperlink support. \DeclareRobustCommand is used by hyperref. Package nameref can be loaded before, after hyperref or after hyperref's definitions in \AtBeginDocument. We have to postpone the definition to \AtBeginDocument to avoid that showkeys overwrites them again.

```
\AddToHook{begindocument}{%
```

\ref

```
  \DeclareDocumentCommand\ref{s}
   {\IfBooleanTF{#1}{\@refstar}{\T@ref}}%
```

\pageref

```
  \DeclareDocumentCommand\pageref{s}
   {\IfBooleanTF{#1}{\@pagerefstar}{\T@pageref}}%
```

\Ref

```
  \DeclareDocumentCommand\Ref{s}
   {\IfBooleanTF{#1}{\@Refstar}{\T@Ref}}%
}
\DeclareHookRule{begindocument}{showkeys}{before}{nameref}
```

4.4 Usage and frontend

Access the (third) name part with \nameref;

\T@nameref

```
\def\T@nameref#1{%
  \NR@ref@showkeys{#1}%
  \begingroup
    \let\label\@gobble
    \NR@setref{#1}\@thirdoffive{#1}%
  \endgroup
}%
```

\@namerefstar

```
\def\@namerefstar#1{%
  \NR@ref@showkeys{#1}%
  \begingroup
    \let\label\@gobble
    \NR@setref{#1}\@thirdoffive{#1}%
  \endgroup
}%
```

\nameref

```
\@ifundefined{nameref}
  {
   \NewDocumentCommand\nameref{s}
    {\IfBooleanTF{#1}{\@namerefstar}{\T@nameref}}
  }
  {
    \PackageWarning{nameref}{Redefining \string\nameref}
    \RenewDocumentCommand\nameref{s}
    {\IfBooleanTF{#1}{\@namerefstar}{\T@nameref}}
  }
```

\Nameref An extended form which gives title and page number. Not really useful, quotes are english, and no starred version. varioref can do that better. Remove??

```
\def\Nameref#1{`\nameref{#1}' on page~\pageref{#1}}
```

\Sectionformat The default for \Sectionformat

```
\providecommand\Sectionformat[2]{#1}
```

4.5 Compatibility with varioref

[This section was derived by Corey Minyard `minyard@acm.org` from the varioref package] Changed in 2019-09-12 by Frank Mittelbach to adapt to changes in varioref

```
\AtBeginDocument{%
  \ifx\csname @@vpageref\endcsname\relax
  \else
```

This requires a varioref newer than 2019-09-12

```
   \let\NR@@vpageref\@@vpageref
   \def\@@vpageref#1[#2]#3{%
      \begingroup
        \csname @safe@activestrue\endcsname
        \edef\x{#3}%
        \@onelevel@sanitize\x
        \toks@{%
          \NR@@vpageref{#1}[{#2}]%
        }%
        \edef\x{\endgroup
          \the\toks@{\x}%
        }%
      \x
    }%
    \DeclareRobustCommand\vnameref[1]{%
      \unskip~\nameref{#1} %
      \@vpageref[\unskip]{#1}%
    }%
  \fi
}
```

4.6 Support for package **listings**

```
\AtBeginDocument{%
  \@ifpackageloaded{listings}{%
    \@ifundefined{NR@nopatch@listings}
     {%
       \let\NROrg@lst@MakeCaption\lst@MakeCaption
       \def\lst@MakeCaption{%
         \ifx\lst@label\@empty
         \else
           \let\@currentlabelname\lst@@caption
         \fi
         \NROrg@lst@MakeCaption
       }%
      }{}%
  }{}%
}
```

⟨/package⟩

5 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols

\@@@ 9
\@@vpageref . . 351, 352
\@Refstar 300, 319
\@auxout 36, 46, 70, 88, 113, 132
\@begintheorem 238, 243, 247
\@bsphack 33, 43, 66, 83, 105
\@caption 187, 188, 194, 195
\@chapter 160, 172
\@currentHref . . . 38, 48, 75, 93, 118, 255
\@currentlabel 37, 47, 72, 90
\@currentlabelname 11, 12, 13, 38, 48, 74, 92, 117, 142, 254, 379
\@empty 8, 14, 208, 305, 377
\@esphack 40, 50, 79, 97, 126
\@fifthoffive 260
\@firstoffive 256, 279, 283
\@for 131
\@fourthoffive 259
\@gobble 325, 332
\@gobble@om 46
\@gobble@som 46
\@ifl@t@r . . . 31, 41, 101
\@ifpackageloaded 19, 183, 201, 237, 372
\@ifundefined . . . 21, 103, 146, 153, 162, 181, 202, 215, 217, 226, 227, 235, 336, 373
\@kernel@reserved@label@data 38, 48
\@namerefstar 329, 339, 344
\@nil 8, 14, 242, 243
\@onelevel@sanitize . 11, 241, 244, 356
\@opargbegintheorem 228, 229
\@pagerefstar . 289, 317
\@part 158, 164
\@refstar 281, 315
\@safe@activesfalse 262, 310
\@safe@activestrue 261, 266, 308
\@schapter . . . 161, 176
\@secondoffive 257, 287, 291
\@sect 144, 146
\@setref 275
\@spart 159, 168
\@ssect 152, 153
\@tempa 112, 123, 131, 133, 134, 207, 208
\@thirdoffive 258, 326, 333
\@undefined 272
\@vpageref 367
\@writetocindents@ 129

A

\AddToHook 313
\AddToHookWithArguments 61
\AtBeginDocument . . . 180, 236, 348, 371

B

\begingroup 20, 34, 44, 67, 85, 107, 130, 239, 265, 324, 331, 353

C

\csname 134, 269, 349, 354

D

\DeclareDocumentCommand 314, 316, 318
\DeclareHookRule . . 321
\DeclareRobustCommand 365
\def 8, 9, 10, 33, 43, 61, 65, 68, 82, 86, 104, 108, 111, 129, 140, 147, 154, 164, 168, 172, 176, 188, 195, 205, 207, 219, 229, 242, 247, 256, 257, 258, 259, 260, 264, 271, 277, 281, 285, 289, 293, 297, 300, 322, 329, 346, 352, 376
\descriptionlabel 218, 219
\do 131

E

\edef 12, 112, 240, 243, 355, 360
\else 54, 209, 306, 350, 378
\endcsname 134, 269, 349, 354
\endgroup 25, 39, 49, 78, 96, 122, 138, 245, 268, 327, 334, 360
\expandafter 13, 122, 243, 245, 267, 269
\ExplSyntaxOff 6
\ExplSyntaxOn 4

F

\fi . 60, 99, 124, 125, 211, 251, 274, 311, 312, 369, 380
\fmtversion . 31, 41, 101

G

\GetTitleString . . . 141
\GetTitleStringResult 142
\global 23
\glossary 46

I

\if@filesw 106

\if@nobreak 124
\IfBooleanTF . . 315, 317, 319, 339, 344
\IfDocumentMetadataT 185
\ifNR@showkeys 17, 81, 304
\ifvmode 124
\ifx . . 53, 208, 246, 272, 305, 349, 377
\immediate 132
\index 46

L

\label 46, 53, 55, 58, 59, 65, 102, 325, 332
\label@hook 27, 69, 87, 109
\label@name 61, 68, 86, 108
\let 5, 46, 58, 59, 102, 110, 142, 144, 152, 158, 159, 160, 161, 187, 194, 204, 218, 228, 238, 273, 325, 332, 351, 375, 379
\long 164, 168, 188, 195, 256, 257, 258, 259, 260
\lst@@caption 379
\lst@label 377
\lst@MakeCaption 375, 376
\LT@c@ption . . 204, 205
\ltx@label 59, 101

M

\MakeUppercase 298
\meaning 243
\MessageBreak . . . 56, 57

N

\Nameref 346
\nameref . . 336, 346, 366
\newcommand 263
\newcounter 145
\NewDocumentCommand 338
\newif 17
\newlabel 37, 47, 71, 89, 114, 133
\nobreak 124
\noexpand 111
\NR@@caption 187, 190, 194, 197
\NR@@setref . . 269, 271
\NR@@vpageref . 351, 358
\NR@chapter . . 160, 174
\NR@gettitle 140, 149, 155, 165, 169, 173, 177, 189, 196, 210, 220, 230, 248
\NR@GlobalAppendToMacro 5, 28
\NR@label@copy 33, 43, 53, 58
\NR@MakeUppercaseFirstOfFive 295, 297, 302
\NR@part 158, 166
\NR@ref@showkeys . . 263, 278, 282, 286, 290, 294, 301, 307, 323, 330
\NR@sanitize@labelname 10, 29
\NR@schapter . 161, 178
\NR@sect 144, 150
\NR@setref 264, 279, 283, 287, 291, 295, 302, 326, 333
\NR@showkeysfalse . . 18
\NR@showkeystrue . . . 23
\NR@spart 159, 170
\NR@ssect 152, 156
\NR@strip@period . 8, 13
\NRorg@begintheorem 238, 249
\NRorg@descriptionlabel 218, 221
\NROrg@lst@MakeCaption 375, 381
\NRorg@LT@c@ption 204, 206
\NRorg@opargbegintheorem 228, 231

P

\PackageWarning 55, 342
\pageref 316, 346
\protect 111
\protected@write 36, 46, 70, 88
\providecommand 27, 254, 255, 261, 262, 347

R

\Ref 318
\ref 314
\relax . . 9, 110, 273, 349
\renewcommand 307
\RenewDocumentCommand 343
\RequirePackage . . . 2, 3

S

\Sectionformat 150, 156, 347
\setcounter 148
\SK@ 84, 309
\SK@@label 84
\SK@@ref 309
\SK@ref 305
\slabel 103
\space 55
\string 37, 47, 55, 71, 89, 114, 133, 240, 342
\strip@period 9

T

\T@nameref 322, 339, 344
\T@pageref . . . 285, 317
\T@Ref 293, 319
\T@ref 277, 315
\the 361
\thepage 37, 47, 73, 91, 110, 116
\thesubequation . . . 115
\tl 5
\toks@ 357, 361

U

\unskip 366, 367
\UseHookWithArguments 35, 45

V

\vnameref 365

W

\write 113, 132

X

\x 240, 241, 246, 355, 356, 360, 361, 363

Y

\y 242, 243

Z

\z 243, 244, 246