

Package ‘CDSE’

April 30, 2024

Type Package

Title 'Copernicus Data Space Ecosystem' API Wrapper

Version 0.2.0

Description Provides interface to the 'Copernicus Data Space Ecosystem' API

<<https://dataspace.copernicus.eu/analyse/apis>>

, mainly for searching the catalog of available data from Copernicus Sentinel missions and obtaining the images for just the area of interest based on selected spectral bands. The package uses the 'Sentinel Hub' REST API interface

<<https://dataspace.copernicus.eu/analyse/apis/sentinel-hub>>

that provides access to various satellite imagery archives. It allows you to access raw satellite data, rendered images, statistical analysis, and other features.

Depends R (>= 3.6.0)

Imports geojsonsf, grDevices, httr2, jsonlite, lubridate, lutz, sf, stats, terra, utils

URL <https://github.com/zivankaraman/CDSE>

BugReports <https://github.com/zivankaraman/CDSE/issues>

License AGPL-3

Encoding UTF-8

Config/build/clean-inst-doc FALSE

RoxygenNote 7.2.2

Suggests maps, parallel, tibble

NeedsCompilation no

Author Zivan Karaman [aut, cre, cph] (<<https://orcid.org/0000-0002-8933-4589>>)

Maintainer Zivan Karaman <zivan.karaman@gmail.com>

Repository CRAN

Date/Publication 2024-04-30 09:30:09 UTC

R topics documented:

CDSE	2
CDSE-deprecated	3
GetArchiveImage	3
GetCollections	5
GetImage	6
GetImageBy...	8
GetOAuthClient	11
GetOAuthToken	12
GetQueryables	13
GetStatistics	14
GetStatisticsBy...	16
Point2Bbox	20
SearchCatalog	21
SearchCatalogBy...	22
SeasonalFilter	25
SeasonalTimerange	26
UniqueCatalog	26
Index	28

CDSE	<i>Package providing interface to the 'Copernicus Data Space Ecosystem' API</i>
------	---

Description

The CDSE package for R was developed to allow access to the 'Copernicus Data Space Ecosystem' <https://dataspace.copernicus.eu/> data and services from R. The 'Copernicus Data Space Ecosystem', deployed in 2023, offers access to the EO data collection from the Copernicus missions, with discovery and download capabilities and numerous data processing tools. In particular, the 'Sentinel Hub' API <https://documentation.dataspace.copernicus.eu/APIs/SentinelHub.html> provides access to the multi-spectral and multi-temporal big data satellite imagery service, capable of fully automated, real-time processing and distribution of remote sensing data and related EO products. Users can use APIs to retrieve satellite data over their AOI and specific time range from full archives in a matter of seconds. When working on the application of EO where the area of interest is relatively small compared to the image tiles distributed by Copernicus (100 x 100 km), it allows to retrieve just the portion of the image of interest rather than downloading the huge tile image file and processing it locally. The goal of the CDSE package is to provide easy access to this functionality from R.

The main functions allow to search the catalog of available imagery from the Sentinel-1, Sentinel-2, Sentinel-3, and Sentinel-5 missions, and to process and download the images of an area of interest and a time range in various formats. Other functions might be added in subsequent releases of the package.

API authentication

Most of the API functions require OAuth2 authentication. The recommended procedure is to obtain an authentication client object from the `GetOAuthClient` function, and to pass it as the `client` argument to the functions requiring the authentication. For more detailed information, you are invited to consult the "Before you start" document.

Project homepage

<https://github.com/zivankaraman/CDSE>

Issues

For bug reports and feature requests please use the tracker <https://github.com/zivankaraman/CDSE/issues>

Author(s)

Zivan Karaman <zivan.karaman@gmail.com>

CDSE-deprecated

Deprecated functions in package CDSE.

Description

The functions listed below are deprecated and will be defunct in the near future. When possible, alternative functions with similar functionality are also mentioned. Help pages for deprecated functions are available at `help("<function>-deprecated")`.

GetArchiveImage

For `GetArchiveImage`, use [GetImage](#).

GetArchiveImage

Get image from the archive (deprecated)

Description

Retrieves the image for the area of interest using the parameters provided.

Arguments

aoi	sf or sfc object, typically a (multi)polygon, describing the Area of Interest.
bbox	numeric vector of four elements describing the bounding box of interest. Specify with a coordinate pair on two (opposite) vertices of the bounding box rectangle. Coordinates need to be in longitude, latitude. Only one of either aoi or bbox may be specified.
time_range	scalar or vector (Date or character that can be converted to date) defining the time interval.
collection	character indicating which collection to search. Must be one of the collections returned by GetCollections.
script	a length one character string containing the evaluation script or the name of the file containing the script.
mosaicking_order	character indicating the order in which tiles are overlapped from which the output result is mosaicked. Must be one of "mostRecent", "leastRecent", or "leastCC". Default: "mostRecent"
file	name of the file to save the image. If NULL, a SpatRaster object is returned. Default: NULL
format	character indicating the output file format. Must be one of "image/tiff", "image/png", or "image/jpeg". Default: "image/tiff"
pixels	integer scalar or length-two vector indicating the request image width and height. Values must be integers between 1 and 2500.
resolution	numeric scalar or length-two vector indicating the spatial resolution of the request image in horizontal and vertical direction (in meters). Only one of the arguments "pixels" or "resolution" must be set at the same time. If the argument "pixels" or "resolution" is scalar, the same value is used for horizontal and vertical direction (width and height).
buffer	numeric, width of the buffer to retrieve the image of enlarged area. Default: 0
mask	logical indicating if the image should contain only pixels within Area of Interest. Default: FALSE
client	OAuth client object to use for authentication.
token	OAuth token character string to use for authentication. Exactly one of either client or token must be specified. It is recommended to use client.
url	character indicating the process endpoint. Default: Copernicus Data Space Ecosystem process endpoint

Details

If aoi argument is provided, the result is returned in the same coordinate reference system.

Value

SpatRaster object (from the package terra) of the requested image (if file is NULL), or the (invisible) name of the file created.

Source

<https://documentation.dataspace.copernicus.eu/APIs/SentinelHub/Process.html>

See Also

[GetCollections](#), [SearchCatalog](#)

[CDSE-deprecated](#)

Examples

```
## Not run:
dsn <- system.file("extdata", "centralpark.geojson", package = "CDSE")
aoi <- sf::read_sf(dsn, as_tibble = FALSE)
script_file <- system.file("scripts", "NDVI_uint8.js", package = "CDSE")
day <- "2023-07-11"
ras <- GetArchiveImage(aoi = aoi, time_range = day, script = script_file,
  collection = "sentinel-2-l2a", format = "image/tiff",
  mosaicking_order = "leastCC", resolution = 10, client = OAuthClient)

## End(Not run)
```

GetCollections

List available collections

Description

Retrieves the list of available imagery collections.

Usage

```
GetCollections(as_data_frame = TRUE, url = getOption("CDSE.catalog_url"))
```

Arguments

`as_data_frame` logical indicating if the result should be returned as data frame. Default: TRUE
`url` character indicating the STAC catalog search endpoint. Default: Copernicus Data Space Ecosystem STAC endpoint

Details

This function doesn't require authentication.

Value

A list or a data.frame of all available imagery collections and their attributes.

Source

<https://documentation.dataspace.copernicus.eu/APIs/SentinelHub/Catalog.html>

See Also

[GetImage](#), [SearchCatalog](#)

Examples

```
## Not run:
GetCollections(as_data_frame = TRUE)

## End(Not run)
```

GetImage

Get image from the archive

Description

Retrieves the image for the area of interest using the parameters provided.

Usage

```
GetImage(
  aoi,
  bbox,
  time_range,
  collection,
  script,
  file = NULL,
  format = c("image/tiff", "image/png", "image/jpeg"),
  mosaicking_order = c("mostRecent", "leastRecent", "leastCC"),
  pixels,
  resolution,
  buffer = 0,
  mask = FALSE,
  client,
  token,
  url = getOption("CDSE.process_url")
)
```

Arguments

aoi	sf or sfc object, typically a (multi)polygon, describing the Area of Interest.
bbox	numeric vector of four elements describing the bounding box of interest. Specify with a coordinate pair on two (opposite) vertices of the bounding box rectangle. Coordinates need to be in longitude, latitude. Only one of either aoi or bbox may be specified.
time_range	scalar or vector (Date or character that can be converted to date) defining the time interval.

collection	character indicating which collection to search. Must be one of the collections returned by GetCollections.
script	a length one character string containing the evaluation script or the name of the file containing the script.
file	name of the file to save the image. If NULL, a SpatRaster object is returned. Default: NULL
format	character indicating the output file format. Must be one of "image/tiff", "image/png", or "image/jpeg". Default: "image/tiff"
mosaicking_order	character indicating the order in which tiles are overlapped from which the output result is mosaicked. Must be one of "mostRecent", "leastRecent", or "leastCC". Default: "mostRecent"
pixels	integer scalar or length-two vector indicating the request image width and height. Values must be integers between 1 and 2500.
resolution	numeric scalar or length-two vector indicating the spatial resolution of the request image in horizontal and vertical direction (in meters). Only one of the arguments "pixels" or "resolution" must be set at the same time. If the argument "pixels" or "resolution" is scalar, the same value is used for horizontal and vertical direction (width and height).
buffer	numeric, width of the buffer to retrieve the image of enlarged area. Default: 0
mask	logical indicating if the image should contain only pixels within Area of Interest. Default: FALSE
client	OAuth client object to use for authentication.
token	OAuth token character string to use for authentication. Exactly one of either client or token must be specified. It is recommended to use client.
url	character indicating the process endpoint. Default: Copernicus Data Space Ecosystem process endpoint

Details

If aoi argument is provided, the result is returned in the same coordinate reference system.

Value

SpatRaster object (from the package terra) of the requested image (if file is NULL), or the (invisible) name of the file created.

Source

<https://documentation.dataspace.copernicus.eu/APIs/SentinelHub/Process.html>

See Also

[GetCollections](#), [SearchCatalog](#)

Examples

```
## Not run:
dsn <- system.file("extdata", "centralpark.geojson", package = "CDSE")
aoi <- sf::read_sf(dsn, as_tibble = FALSE)
script_file <- system.file("scripts", "NDVI_uint8.js", package = "CDSE")
day <- "2023-07-11"
ras <- GetImage(aoi = aoi, time_range = day, script = script_file,
  collection = "sentinel-2-l2a", format = "image/tiff",
  mosaicking_order = "leastCC", resolution = 10, client = OAuthClient)

## End(Not run)
```

GetImageBy...

Get image from the archive (vectorization ready)

Description

These functions retrieve the image for the area of interest using the parameters provided. They are simple wrappers around the 'GetImage' function with arguments organized in a way that facilitates calling the function in a vectorized manner (using 'lapply' or similar function) and thus potentially also the parallelization.

Usage

```
GetImageByTimerange(
  time_range,
  aoi,
  bbox,
  collection,
  script,
  file = NULL,
  format = c("image/tiff", "image/png", "image/jpeg"),
  mosaicking_order = c("mostRecent", "leastRecent", "leastCC"),
  pixels,
  resolution,
  buffer = 0,
  mask = FALSE,
  client,
  token,
  url = getOption("CDSE.process_url")
)
```

```
GetImageByAOI(
  aoi,
  time_range,
  collection,
  script,
```



```

    file = NULL,
    format = c("image/tiff", "image/png", "image/jpeg"),
    mosaicking_order = c("mostRecent", "leastRecent", "leastCC"),
    pixels,
    resolution,
    buffer = 0,
    mask = FALSE,
    client,
    token,
    url = getOption("CDSE.process_url")
)

```

```

GetImageByBbox(
  bbox,
  time_range,
  collection,
  script,
  file = NULL,
  format = c("image/tiff", "image/png", "image/jpeg"),
  mosaicking_order = c("mostRecent", "leastRecent", "leastCC"),
  pixels,
  resolution,
  buffer = 0,
  mask = FALSE,
  client,
  token,
  url = getOption("CDSE.process_url")
)

```

Arguments

time_range	scalar or vector (Date or character that can be converted to date) defining the time interval.
aoi	sf or sfc object, typically a (multi)polygon, describing the Area of Interest.
bbox	numeric vector of four elements describing the bounding box of interest. Specify with a coordinate pair on two (opposite) vertices of the bounding box rectangle. Coordinates need to be in longitude, latitude. Only one of either aoi or bbox may be specified.
collection	character indicating which collection to search. Must be one of the collections returned by GetCollections.
script	a length one character string containing the evaluation script or the name of the file containing the script.
file	name of the file to save the image. If NULL, a SpatRaster object is returned. Default: NULL
format	character indicating the output file format. Must be one of "image/tiff", "image/png", or "image/jpeg". Default: "image/tiff"

<code>mosaicking_order</code>	character indicating the order in which tiles are overlapped from which the output result is mosaicked. Must be one of "mostRecent", "leastRecent", or "leastCC". Default: "mostRecent"
<code>pixels</code>	integer scalar or length-two vector indicating the request image width and height. Values must be integers between 1 and 2500.
<code>resolution</code>	numeric scalar or length-two vector indicating the spatial resolution of the request image in horizontal and vertical direction (in meters). Only one of the arguments "pixels" or "resolution" must be set at the same time. If the argument "pixels" or "resolution" is scalar, the same value is used for horizontal and vertical direction (width and height).
<code>buffer</code>	numeric, width of the buffer to retrieve the image of enlarged area. Default: 0
<code>mask</code>	logical indicating if the image should contain only pixels within Area of Interest. Default: FALSE
<code>client</code>	OAuth client object to use for authentication.
<code>token</code>	OAuth token character string to use for authentication. Exactly one of either <code>client</code> or <code>token</code> must be specified. It is recommended to use <code>client</code> .
<code>url</code>	character indicating the process endpoint. Default: Copernicus Data Space Ecosystem process endpoint

Details

If `aoi` argument is provided, the result is returned in the same coordinate reference system.

`GetImageByTimeRange` is arranged for vectorization on `time_range` (`time_range` is the first argument).

`GetImageByAOI` is arranged for vectorization on `aoi` (`aoi` is the first argument).

`GetImageByBbox` is arranged for vectorization on `bbox` (`bbox` is the first argument).

Value

`SpatRaster` object (from the package `terra`) of the requested image (if `file` is NULL), or the (invisible) name of the file created.

Source

<https://documentation.dataspace.copernicus.eu/APIs/SentinelHub/Process.html>

See Also

[GetImage](#)

Examples

```
## Not run:
dsn <- system.file("extdata", "centralpark.geojson", package = "CDSE")
aoi <- sf::read_sf(dsn, as_tibble = FALSE)
cloudless_images <- SearchCatalog(aoi = aoi, from = "2023-01-01", to = "2023-12-31",
  collection = "sentinel-2-l2a", with_geometry = TRUE,
  filter = "eo:cloud_cover < 0.8", client = OAuthClient)
script_file <- system.file("scripts", "NDVI_float32.js", package = "CDSE")
days <- rev(cloudless_images$acquisitionDate)
lstRast <- lapply(days, GetImageByTimerange, aoi = aoi, collection = "sentinel-2-l2a",
  script = script_file, file = NULL, format = "image/tiff", mosaicking_order = "mostRecent",
  resolution = 10, buffer = 0, mask = TRUE, client = OAuthClient,
  url = getOption("CDSE.process_url"))
par(mfrow = c(3, 4))
sapply(seq_along(days), FUN = function(i) {
  ras <- lstRast[[i]]
  day <- days[i]
  ras[ras < 0] <- 0
  terra::plot(ras, main = paste("Central Park NDVI on", day), range = c(0, 1),
    cex.main = 0.7, pax = list(cex.axis = 0.5), plg = list(cex = 0.5),
    col = colorRampPalette(c("darkred", "yellow", "darkgreen"))(99))
})

## End(Not run)
```

 GetOAuthClient

Get OAuth client

Description

Gets an OAuth authentication client (httr2 OAuth client object)

Usage

```
GetOAuthClient(id, secret, url = getOption("CDSE.auth_url"))
```

Arguments

<code>id</code>	character, user OAuth client id
<code>secret</code>	character, user OAuth client secret
<code>url</code>	character, endpoint for requesting tokens. Default: Copernicus Data Space Ecosystem OAuth endpoint

Details

The client can be used in queries requiring the authentication.

Value

httr2 OAuth client object

Source

<https://documentation.dataspace.copernicus.eu/APIs/SentinelHub/Overview/Authentication.html>

See Also

[GetOAuthToken](#)

Examples

```
## Not run:  
id <- "..."  
secret <- "..."  
OAuthClient <- GetOAuthClient(id = id, secret = secret)  
  
## End(Not run)
```

GetOAuthToken

Get OAuth token

Description

Gets an OAuth authentication token (long character string)

Usage

```
GetOAuthToken(id, secret, url = getOption("CDSE.auth_url"))
```

Arguments

id	character, user OAuth client id
secret	character, user OAuth client secret
url	character, endpoint for requesting tokens. Default: Copernicus Data Space Ecosystem OAuth endpoint

Details

The token can be used in queries requiring the authentication.

Value

Long character string containing the authentication token.

Source

<https://documentation.dataspace.copernicus.eu/APIs/SentinelHub/Overview/Authentication.html>

See Also

[GetOAuthClient](#)

Examples

```
## Not run:
id <- "... "
secret <- "... "
token <- GetOAuthToken(id = id, secret = secret)

## End(Not run)
```

GetQueryables

Get CQL2 parameters for a collection

Description

Returns a list of variable terms that can be used in CQL2 expressions to filter the collection catalog search.

Usage

```
GetQueryables(
  collection,
  as_data_frame = TRUE,
  client,
  token,
  url = getOption("CDSE.catalog_url")
)
```

Arguments

collection	character indicating the collection for which the parameters are queried. Must be one of the collections returned by <code>GetCollections</code> .
as_data_frame	logical indicating if the result should be returned as data frame. Default: TRUE
client	OAuth client object to use for authentication.
token	OAuth token character string to use for authentication. Exactly one of either <code>client</code> or <code>token</code> must be specified. It is recommended to use <code>client</code> .
url	character indicating the STAC catalog search endpoint. Default: Copernicus Data Space Ecosystem STAC endpoint

Details

If no parameters found, a NULL value or 0-row data.frame is returned.

Value

A list or a data.frame.

Source

https://documentation.dataspace.copernicus.eu/APIs/SentinelHub/ApiReference.html#tag/catalog_collections/operation/getCatalogCollectionQueryables

See Also

[GetCollections](#), [SearchCatalog](#)

Examples

```
## Not run:  
GetQueryables("sentinel-2-12a", client = OAuthClient)  
  
## End(Not run)
```

GetStatistics

Get statistical values

Description

Retrieves the simple statistics for the area of interest calculated based on satellite imagery without having to download images.

Usage

```
GetStatistics(  
  aoi,  
  bbox,  
  time_range,  
  collection,  
  script,  
  mosaicking_order = c("mostRecent", "leastRecent", "leastCC"),  
  pixels,  
  resolution,  
  buffer = 0,  
  percentiles = NULL,  
  aggregation_period = 1L,  
  lastIntervalBehavior = c("SKIP", "SHORTEN", "EXTEND"),  
  as_data_frame = TRUE,  
  client,
```

```

    token,
    url = getOption("CDSE.statistical_url")
)

```

Arguments

aoi	sf or sfc object, typically a (multi)polygon, describing the Area of Interest.
bbox	numeric vector of four elements describing the bounding box of interest. Specify with a coordinate pair on two (opposite) vertices of the bounding box rectangle. Coordinates need to be in longitude, latitude. Only one of either aoi or bbox may be specified.
time_range	scalar or vector (Date or character that can be converted to date) defining the time interval.
collection	character indicating which collection to search. Must be one of the collections returned by GetCollections.
script	a length one character string containing the evaluation script or the name of the file containing the script.
mosaicking_order	character indicating the order in which tiles are overlapped from which the output result is mosaicked. Must be one of "mostRecent", "leastRecent", or "leastCC". Default: "mostRecent"
pixels	integer scalar or length-two vector indicating the request image width and height. Values must be integers between 1 and 2500.
resolution	numeric scalar or length-two vector indicating the spatial resolution of the request image in horizontal and vertical direction (in meters). Only one of the arguments "pixels" or "resolution" must be set at the same time. If the argument "pixels" or "resolution" is scalar, the same value is used for horizontal and vertical direction (width and height).
buffer	numeric, width of the buffer to retrieve the image of enlarged area. Default: 0
percentiles	numeric vector indicating which percentile values should be computed. Default: NULL, don't compute any percentiles.
aggregation_period	the length of the aggregation period in days. Default: 1
lastIntervalBehavior	= c("SKIP", "SHORTEN", "EXTEND")
as_data_frame	logical indicating if the result should be returned as data frame. Default: TRUE
client	OAuth client object to use for authentication.
token	OAuth token character string to use for authentication. Exactly one of either client or token must be specified. It is recommended to use client.
url	character indicating the process endpoint. Default: Copernicus Data Space Ecosystem process endpoint

Details

The values are aggregated over the period (number of days) given by the `aggregation_period` argument. The default value 1 provides daily statistics. The statistics are returned only for the days when the data is available (the days of the satellite overpass).

The scripts used for the Statistical API have some additional requirements: the `evaluatePixel()` function must, in addition to other output, always also return `dataMask` output. This output defines which pixels are excluded from calculations. For more information please visit the on-line documentation <https://documentation.dataspace.copernicus.eu/APIs/SentinelHub/Statistical.html>.

If percentiles requested are 25, 50, and 75, the columns are renamed 'q1', 'median', and 'q3'.

Value

`data.frame` or `list` with statistical values.

Source

<https://documentation.dataspace.copernicus.eu/APIs/SentinelHub/Statistical.html>

See Also

[GetCollections](#), [SearchCatalog](#)

Examples

```
## Not run:
dsn <- system.file("extdata", "centralpark.geojson", package = "CDSE")
aoi <- sf::read_sf(dsn, as_tibble = FALSE)
script_file <- system.file("scripts", "NDVI_CLOUDS_STAT.js", package = "CDSE")
daily_stats <- GetStatistics(aoi = aoi, time_range = c("2023-07-01", "2023-07-31"),
  collection = "sentinel-2-l2a", script = script_file, mosaicking_order = "leastCC",
  resolution = 100, aggregation_period = 1, client = OAuthClient)
weekly_stats <- GetStatistics(aoi = aoi, time_range = c("2023-07-01", "2023-07-31"),
  collection = "sentinel-2-l2a", script = script_file, mosaicking_order = "leastCC",
  resolution = 100, aggregation_period = 7, client = OAuthClient)
weekly_stats_extended <- GetStatistics(aoi = aoi, time_range = c("2023-07-01", "2023-07-31"),
  collection = "sentinel-2-l2a", script = script_file, mosaicking_order = "leastCC",
  resolution = 100, aggregation_period = 7, lastIntervalBehavior = "EXTEND", client = OAuthClient)

## End(Not run)
```

GetStatisticsBy... *Get statistical values (vectorization ready)*

Description

These functions retrieve simple statistics for the area of interest calculated based on satellite imagery without having to download images. They are simple wrappers around the 'GetStatistics' function with arguments organized in a way that facilitates calling the function in a vectorized manner (using 'lapply' or similar function) and thus potentially also the parallelization.

Usage

```
GetStatisticsByTimerange(  
  time_range,  
  aoi,  
  bbox,  
  collection,  
  script,  
  mosaicking_order = c("mostRecent", "leastRecent", "leastCC"),  
  pixels,  
  resolution,  
  buffer = 0,  
  percentiles = NULL,  
  aggregation_period = 1L,  
  as_data_frame = TRUE,  
  client,  
  token,  
  url = getOption("CDSE.statistical_url")  
)
```

```
GetStatisticsByAOI(  
  aoi,  
  time_range,  
  collection,  
  script,  
  mosaicking_order = c("mostRecent", "leastRecent", "leastCC"),  
  pixels,  
  resolution,  
  buffer = 0,  
  percentiles = NULL,  
  aggregation_period = 1L,  
  as_data_frame = TRUE,  
  client,  
  token,  
  url = getOption("CDSE.statistical_url")  
)
```

```
GetStatisticsByBbox(  
  bbox,  
  time_range,  
  collection,  
  script,
```

```

mosaicking_order = c("mostRecent", "leastRecent", "leastCC"),
pixels,
resolution,
buffer = 0,
percentiles = NULL,
aggregation_period = 1L,
as_data_frame = TRUE,
client,
token,
url = getOption("CDSE.statistical_url")
)

```

Arguments

<code>time_range</code>	scalar or vector (Date or character that can be converted to date) defining the time interval.
<code>aoi</code>	sf or sfc object, typically a (multi)polygon, describing the Area of Interest.
<code>bbox</code>	numeric vector of four elements describing the bounding box of interest. Specify with a coordinate pair on two (opposite) vertices of the bounding box rectangle. Coordinates need to be in longitude, latitude. Only one of either <code>aoi</code> or <code>bbox</code> may be specified.
<code>collection</code>	character indicating which collection to search. Must be one of the collections returned by <code>GetCollections</code> .
<code>script</code>	a length one character string containing the evaluation script or the name of the file containing the script.
<code>mosaicking_order</code>	character indicating the order in which tiles are overlapped from which the output result is mosaicked. Must be one of "mostRecent", "leastRecent", or "leastCC". Default: "mostRecent"
<code>pixels</code>	integer scalar or length-two vector indicating the request image width and height. Values must be integers between 1 and 2500.
<code>resolution</code>	numeric scalar or length-two vector indicating the spatial resolution of the request image in horizontal and vertical direction (in meters). Only one of the arguments "pixels" or "resolution" must be set at the same time. If the argument "pixels" or "resolution" is scalar, the same value is used for horizontal and vertical direction (width and height).
<code>buffer</code>	numeric, width of the buffer to retrieve the image of enlarged area. Default: 0
<code>percentiles</code>	numeric vector indicating which percentile values should be computed. Default: NULL, don't compute any percentiles.
<code>aggregation_period</code>	the length of the aggregation period in days. Default: 1
<code>as_data_frame</code>	logical indicating if the result should be returned as data frame. Default: TRUE
<code>client</code>	OAuth client object to use for authentication.
<code>token</code>	OAuth token character string to use for authentication. Exactly one of either <code>client</code> or <code>token</code> must be specified. It is recommended to use <code>client</code> .

`url` character indicating the process endpoint. Default: Copernicus Data Space Ecosystem process endpoint

Details

The values are aggregated over the period (number of days) given by the `aggregation_period` argument. The default value 1 provides daily statistics. The statistics are returned only for the days when the data is available (the days of the satellite overpass).

The scripts used for the Statistical API have some additional requirements: the `evaluatePixel()` function must, in addition to other output, always also return `dataMask` output. This output defines which pixels are excluded from calculations. For more information please visit the on-line documentation <https://documentation.dataspace.copernicus.eu/APIs/SentinelHub/Statistical.html>.

If percentiles requested are 25, 50, and 75, the columns are renamed 'q1', 'median', and 'q3'.

`GetStatisticsByTimerange` is arranged for vectorization on `time_range` (`time_range` is the first argument).

`GetStatisticsByAOI` is arranged for vectorization on `aoi` (`aoi` is the first argument).

`GetStatisticsByBbox` is arranged for vectorization on `bbox` (`bbox` is the first argument).

Value

data.frame or list with statistical values.

Source

<https://documentation.dataspace.copernicus.eu/APIs/SentinelHub/Statistical.html>

See Also

[GetCollections](#), [SearchCatalog](#), [GetStatistics](#)

Examples

```
## Not run:
dsn <- system.file("extdata", "centralpark.geojson", package = "CDSE")
aoi <- sf::read_sf(dsn, as_tibble = FALSE)
script_file <- "inst/scripts/NDVI_dataMask_float32.js"
seasons <- SeasonalTimerange(from = "2020-06-01", to = "2023-08-31")
lst_stats <- lapply(seasons, GetStatisticsByTimerange, aoi = aoi, collection = "sentinel-2-l2a",
  script = script_file, mosaicking_order = "leastCC", resolution = 100,
  aggregation_period = 7L, client = OAuthClient)
weekly_stats <- do.call(rbind, lst_stats)
weekly_stats <- weekly_stats[rev(order(weekly_stats$from)), ]
row.names(weekly_stats) <- NULL
head(weekly_stats)

## End(Not run)
```

Point2Bbox*Create bounding box around a point*

Description

Creates the bounding box (numeric vector of length four) around the input point(s).

Usage

```
Point2Bbox(x, y = NULL, size, crs = 4326)
```

Arguments

x	an sf, sfc, or SpatialPoints* object, a numeric indicating the longitude/easting of the point(s), or any input accepted by <code>xy.coords</code>
y	numeric, the latitude/northing of the point(s). Default: NULL
size	numeric indicating the size (in meters) of the bounding box to create
crs	coordinate reference system of the input (and the output): object of class <code>crs</code> , or input string for <code>st_crs</code> . Default: 4326 (WGS 84)

Details

The function assumes that the `crs` units are either degrees or meters, a warning is issued if not, and the result will probably be incorrect.

Value

A bounding box (numeric vector of length four), or a list of bounding boxes if the input is not scalar.

See Also

[xy.coords](#), [st_crs](#)

Examples

```
## Not run:  
Point2Bbox(x = -73.96557, y = 40.78246, size = 1000, crs = 4326)  
  
## End(Not run)
```

SearchCatalog	<i>Search collection for available images</i>
---------------	---

Description

Searches the specified collection for available images in the given time interval and intersecting with the bounding box or the area of interest.

Usage

```
SearchCatalog(
  aoi,
  bbox,
  from,
  to,
  collection,
  as_data_frame = TRUE,
  with_geometry = TRUE,
  filter = NULL,
  client,
  token,
  url = getOption("CDSE.catalog_url")
)
```

Arguments

aoi	sf or sfc object, typically a (multi)polygon, describing the Area of Interest.
bbox	numeric vector of four elements describing the bounding box of interest. Specify with a coordinate pair on two (opposite) vertices of the bounding box rectangle. Coordinates need to be in longitude, latitude. Only one of either aoi or bbox may be specified.
from	start of the time interval to search.
to	end of the time interval to search. from and to can be either Date or character that can be converted to date by as.Date. Open interval (one side only) can be obtained by providing the NA or NULL value for the corresponding argument.
collection	character indicating which collection to search. Must be one of the collections returned by GetCollections.
as_data_frame	logical indicating if the result should be returned as data frame. Default: TRUE
with_geometry	logical indicating if the granule geometries should be included in the data.frame. Default: TRUE
filter	character, CQL2 text filter. Use the function GetQueryables to find out which filters can be used with the collection. Default: NULL (no filtering)

<code>client</code>	OAuth client object to use for authentication.
<code>token</code>	OAuth token character string to use for authentication.
	Exactly one of either <code>client</code> or <code>token</code> must be specified. It is recommended to use <code>client</code> .
<code>url</code>	character indicating the STAC catalog search endpoint. Default: Copernicus Data Space Ecosystem STAC endpoint

Details

If no images found, a NULL value is returned.

Value

A list, data.frame or a sf object.

Source

<https://documentation.dataspace.copernicus.eu/APIs/SentinelHub/Catalog.html>

See Also

[GetCollections](#), [GetQueryables](#), [GetImage](#)

Examples

```
## Not run:
dsn <- system.file("extdata", "luxembourg.geojson", package = "CDSE")
aoi <- sf::read_sf(dsn, as_tibble = FALSE)
images <- SearchCatalog(aoi = aoi, from = "2023-07-01", to = "2023-07-31",
  collection = "sentinel-2-l2a", with_geometry = TRUE, client = OAuthClient)
images_cloudless <- SearchCatalog(aoi = aoi, from = "2023-07-01", to = "2023-07-31",
  filter = "eo:cloud_cover < 5",
  collection = "sentinel-2-l2a", with_geometry = TRUE, client = OAuthClient)

## End(Not run)
```

SearchCatalogBy... *Search collection for available images (vectorization ready)*

Description

These functions search the specified collection for available images using the parameters provided. They are simple wrappers around the 'SearchCatalog' function with arguments organized in a way that facilitates calling the function in a vectorized manner (using 'lapply' or similar function) and thus potentially also the parallelization. The 'from' and 'to' arguments are combined into a single argument 'time_range'.

Usage

```
SearchCatalogByTimerange(
  time_range,
  aoi,
  bbox,
  collection,
  as_data_frame = TRUE,
  with_geometry = TRUE,
  filter = NULL,
  client,
  token,
  url = getOption("CDSE.catalog_url")
)
```

```
SearchCatalogByAOI(
  aoi,
  time_range,
  collection,
  as_data_frame = TRUE,
  with_geometry = TRUE,
  filter = NULL,
  client,
  token,
  url = getOption("CDSE.catalog_url")
)
```

```
SearchCatalogByBbox(
  bbox,
  time_range,
  collection,
  as_data_frame = TRUE,
  with_geometry = TRUE,
  filter = NULL,
  client,
  token,
  url = getOption("CDSE.catalog_url")
)
```

Arguments

<code>time_range</code>	scalar or vector (Date or character that can be converted to date) defining the time interval. Open interval (one side only) can be obtained by providing the NA or NULL value for the corresponding argument.
<code>aoi</code>	sf or sfc object, typically a (multi)polygon, describing the Area of Interest.
<code>bbox</code>	numeric vector of four elements describing the bounding box of interest. Specify with a coordinate pair on two (opposite) vertices of the bounding box rectangle. Coordinates need to be in longitude, latitude. Only one of either <code>aoi</code> or <code>bbox</code> may be specified.

collection	character indicating which collection to search. Must be one of the collections returned by GetCollections.
as_data_frame	logical indicating if the result should be returned as data frame. Default: TRUE
with_geometry	logical indicating if the granule geometries should be included in the data.frame. Default: TRUE
filter	character, CQL2 text filter. Use the function GetQueryables to find out which filters can be used with the collection. Default: NULL (no filtering)
client	OAuth client object to use for authentication.
token	OAuth token character string to use for authentication. Exactly one of either client or token must be specified. It is recommended to use client.
url	character indicating the STAC catalog search endpoint. Default: Copernicus Data Space Ecosystem STAC endpoint

Details

If no images found, a NULL value is returned.

SearchCatalogByTimerange is arranged for vectorization on time_range (time_range is the first argument).

SearchCatalogByAOI is arranged for vectorization on aoi (aoi is the first argument).

SearchCatalogByBbox is arranged for vectorization on bbox (bbox is the first argument).

Value

A list, data.frame or a sf object.

Source

<https://documentation.dataspace.copernicus.eu/APIs/SentinelHub/Catalog.html>

See Also

[SearchCatalog](#)

Examples

```
## Not run:
dsn <- system.file("extdata", "centralpark.geojson", package = "CDSE")
aoi <- sf::read_sf(dsn, as_tibble = FALSE)
seasons <- SeasonalTimerange(from = "2020-06-01", to = "2023-08-31")
lst_images_cloudless <- lapply(seasons, SearchCatalogByTimerange, aoi = aoi,
  collection = "sentinel-2-l2a", with_geometry = FALSE,
  filter = "eo:cloud_cover < 5", client = OAuthClient)
images_cloudless <- do.call(rbind, lst_images_cloudless)
images_cloudless <- images_cloudless[rev(order(images_cloudless$acquisitionDate)), ]
row.names(images_cloudless) <- NULL
head(images_cloudless[, 1:5])

## End(Not run)
```

`SeasonalFilter`*Filter image catalog for seasonal images*

Description

Filters image catalog entries that fall in the season of interest - dates between from day/month and to day/month for all years in the from - to time range.

Usage

```
SeasonalFilter(catalog, from, to)
```

Arguments

`catalog` `data.frame` or `sf` object as the one produced by a call to `SearchCatalog`

`from` start of the season of interest.

`to` end of the season of interest.

The `from` and `to` arguments can be either `Date` or character that can be converted to date by `as.Date`. Open intervals are not allowed (both `from` and `to` must be valid dates).

Value

A `data.frame` or a `sf` object, depending on the type of the input.

See Also

[SearchCatalog](#), [SeasonalTimerange](#)

Examples

```
## Not run:
dsn <- system.file("extdata", "centralpark.geojson", package = "CDSE")
aoi <- sf::read_sf(dsn, as_tibble = FALSE)
all_images <- SearchCatalog(aoi = aoi, from = "2021-06-01", to = "2023-08-31",
  collection = "sentinel-2-l2a", with_geometry = TRUE, client = OAuthClient)
seasonal_images <- SeasonalFilter(all_images, from = "2021-06-01", to = "2023-08-31")

## End(Not run)
```

SeasonalTimerange *Create seasonal time range*

Description

Creates list of seasonal filters (one per year) for the season of interest - dates between from day/month and to day/month for all years in the from - to time range.

Usage

```
SeasonalTimerange(from, to)
```

Arguments

from start of the season of interest.
to end of the season of interest.
The from and to arguments can be either Date or character that can be converted to date by as.Date. Open intervals are not allowed (both from and to must be valid dates).

Value

A list of time ranges defining the season of interest for each year.

Examples

```
## Not run:
seasons <- SeasonalTimerange(from = "2020-05-01", to = "2023-09-30")
seasons <- SeasonalTimerange(from = "2019-11-01", to = "2023-03-30")

## End(Not run)
```

UniqueCatalog *Produce image catalog without multiple entries per date*

Description

Sometimes several images could be available for the given day. It can be useful to have a list where for any given day there is just one row in the list. This unique row can be selected to represent either the least cloud coverage or the biggest coverage of the are of interest.

Usage

```
UniqueCatalog(
  imageCatalog,
  by = c("areaCoverage", "tileCloudCover"),
  keep = names(imageCatalog)
)
```

Arguments

imageCatalog	data.frame as returned by the SearchCatalog function.
by	character indicating which attribute is used to select the best image per date. Can be either "areaCoverage" or "tileCloudCover".
keep	list of columns to keep in output. Default: all columns in input.

Details

By default, the returned data.frame has the same columns as the input catalog. User can specify a subset of columns to include in the output through the keep parameter.

Value

data.frame with one row per date.

See Also

[SearchCatalog](#)

Examples

```
## Not run:
dsn <- system.file("extdata", "luxembourg.geojson", package = "CDSE")
aoi <- sf::read_sf(dsn, as_tibble = FALSE)
images <- SearchCatalog(aoi = aoi, from = "2023-07-01", to = "2023-07-31",
  collection = "sentinel-2-l2a", with_geometry = TRUE, client = OAuthClient)
best_daily <- UniqueCatalog(images, by = "areaCoverage",
  keep = c("acquisitionDate", "tileCloudCover", "areaCoverage", "satellite"))

## End(Not run)
```

Index

CDSE, [2](#)
CDSE-deprecated, [3](#)

GetArchiveImage, [3](#)
GetCollections, [5](#), [5](#), [7](#), [14](#), [16](#), [19](#), [22](#)
GetImage, [3](#), [6](#), [6](#), [10](#), [22](#)
GetImageBy..., [8](#)
GetImageByAOI (GetImageBy...), [8](#)
GetImageByBbox (GetImageBy...), [8](#)
GetImageByTimerange (GetImageBy...), [8](#)
GetOAuthClient, [11](#), [13](#)
GetOAuthToken, [12](#), [12](#)
GetQueryables, [13](#), [22](#)
GetStatistics, [14](#), [19](#)
GetStatisticsBy..., [16](#)
GetStatisticsByAOI
 (GetStatisticsBy...), [16](#)
GetStatisticsByBbox
 (GetStatisticsBy...), [16](#)
GetStatisticsByTimerange
 (GetStatisticsBy...), [16](#)

Point2Bbox, [20](#)

SearchCatalog, [5](#)–[7](#), [14](#), [16](#), [19](#), [21](#), [24](#), [25](#), [27](#)
SearchCatalogBy..., [22](#)
SearchCatalogByAOI
 (SearchCatalogBy...), [22](#)
SearchCatalogByBbox
 (SearchCatalogBy...), [22](#)
SearchCatalogByTimerange
 (SearchCatalogBy...), [22](#)
SeasonalFilter, [25](#)
SeasonalTimerange, [25](#), [26](#)
st_crs, [20](#)

UniqueCatalog, [26](#)

xy.coords, [20](#)