

Package ‘mxmmod’

October 13, 2022

Type Package

Title Measurement Model of Derivatives in 'OpenMx'

Version 1.1.0

Description Provides a convenient interface in 'OpenMx' for building Estabrook's (2015) <[doi:10.1037/a0034523](https://doi.org/10.1037/a0034523)> Measurement Model of Derivatives (MMOD).

License Apache License 2.0

Encoding UTF-8

LazyData true

Imports OpenMx

Suggests knitr, rmarkdown, testthat, tidyverse

VignetteBuilder knitr

RoxygenNote 7.1.1

Depends R (>= 2.10)

NeedsCompilation no

Author Kyle D. Husmann [aut, cre],
Timothy R. Brick [aut],
Ryne Estabrook [aut]

Maintainer Kyle D. Husmann <kdh38@psu.edu>

Repository CRAN

Date/Publication 2021-05-18 15:40:02 UTC

R topics documented:

mxMmodModel	2
nlsy97depression	3

Index	4
--------------	----------

 mxMmodModel

Create an MMOD

Description

This function builds a Measurement Model of Derivatives (MMOD; Estabrook 2015) with a given factor structure.

Usage

```
mxMmodModel(
  data,
  modelName,
  idvar,
  timevar,
  structure,
  orthogonal = F,
  embed_dim = NULL,
  fiml = F
)
```

Arguments

<code>data</code>	a data frame with measurements in long format
<code>modelName</code>	name for the resulting model
<code>idvar</code>	name of column for subject IDs
<code>timevar</code>	name of column for measurement occasion
<code>structure</code>	factor structure, see 'Details'
<code>orthogonal</code>	if true, fix correlations between factors to 0 (A factor and its derivatives will still intercorrelate)
<code>embed_dim</code>	time delay embedding dimension
<code>fiml</code>	if true, use raw data to fit model with FIML. Otherwise, fit using cov matrix (dropping missing values if necessary).

Details

The structure argument is a list of latent factors and their mappings to manifest variables. For example, a one factor structure would be:

```
list(F1 = c('m1', 'm2', 'm3', 'm4', 'm5', 'm6'))
```

And a two factor structure would be:

```
list(F1 = c('m1', 'm2', 'm3'), F2 = c('m4', 'm5', 'm6'))
```

Value

an MMOD as an mxModel object

Examples

```
data(nlsy97depression)
# Fit one factor MMOD
structure <- list(
  F1 = c('nervous', 'down', 'depressed', 'calm', 'happy')
)
mmod_model <- mxMmodModel(data=nlsy97depression,
                          modelName='1 Factor MMOD',
                          idvar='pid', timevar='occasion', structure=structure)
mmod_fit <- OpenMx::mxRun(mmod_model)
summary(mmod_fit)
```

nlsy97depression *NLSY97 Longitudinal Depression Scale Data*

Description

A 5-item depression scale used on the National Longitudinal Survey of Youth, 1997 sample (NLSY97). Individuals were assessed in 2000, 2002, and 2004. All items are assessed on a 4-point likert scale.

Usage

```
nlsy97depression
```

Format

A data frame with 26952 rows and 7 variables:

pid Unique ID of participant
sex Sex of participant
birth_m Birth Month
birth_y Birth Year
occasion Measurement occasion
nervous How often participant felt 'like a nervous person'
calm How often participant felt 'calm and peaceful'
down How often participant felt 'down or blue'
happy How often participant felt 'like a happy person'
depressed How often participant felt 'depressed'

Source

<https://www.bls.gov/nls/nlsy97.htm>

Index

* **datasets**

nlsy97depression, [3](#)

mxMmodModel, [2](#)

nlsy97depression, [3](#)