

Package ‘writeLog’

October 15, 2026

Title Write Printed Output of R Objects to Log Files

Version 0.1.0

Description Provides writeLog(), a small helper that writes the printed output of a named list of R objects to a text file in a log directory, one element after another, each preceded by its list name as a heading. Supports versioned file names and appending to an existing log file.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.3

Suggests testthat (>= 3.0.0), withr

Config/testthat/edition 3

URL <https://github.com/jeffzifanwu/writeLog>

BugReports <https://github.com/jeffzifanwu/writeLog/issues>

NeedsCompilation no

Author Jeffzifan Wu [aut, cre]

Maintainer Jeffzifan Wu <zifan.jeffwu@gmail.com>

Repository CRAN

Date/Publication 2026-10-15 16:10:02 UTC

Contents

writeLog	2
Index	3

writeLog	<i>Write the printed output of each element of a named list to a .txt file in logDir, one after another, each preceded by its list name as a heading.</i>
----------	---

Description

Write the printed output of each element of a named list to a .txt file in logDir, one after another, each preceded by its list name as a heading.

Usage

```
writeLog(
  x,
  fileName = "log",
  version = NULL,
  desc = NULL,
  logDir,
  append = FALSE
)
```

Arguments

x	Named list of objects to print/log, e.g. list(int.orig = summary(int), int.hp = halvorsenPalmquist(int)).
fileName	Name of the log file, without extension (e.g. "aq_bdr").
version	Version label prepended to fileName (e.g. "v1"). The file is written as logDir/version_fileName.txt; if NULL, the version prefix and its separator are dropped.
desc	Description to print at the top of the log file.
logDir	Directory to write the log file to, e.g. tempdir(). Created if missing. There is no default, so the package never writes to the working directory or home filespace unless you ask it to.
append	If TRUE, add to the log file when it already exists rather than overwriting it; if it does not exist, a new file is created. If FALSE (the default), any existing file is overwritten.

Value

x, invisibly (so this can be used inline without breaking a pipe).

Examples

```
tmp <- tempfile()
writeLog(list(one = 1:3, summary = summary(1:10)),
  fileName = "example", logDir = tmp)
readLines(file.path(tmp, "example.txt"))
```

Index

`writeLog`, [2](#)